

Claim Amendments

1. (Once Amended) A method for making formation evaluation determinations evaluating formation fluids, comprising:
 - acquiring a nuclear magnetic resonance measurement of an earth formation;
 - acquiring a dielectric measurement of the earth formation; and
 - determining an oil volume fraction of the earth formation from a combination of the nuclear magnetic resonance measurement and the dielectric measurement.
2. (Original) The method of claim 1, wherein the nuclear magnetic resonance measurement comprises at least one spin echo amplitude.
3. (Original) The method of claim 2, wherein the acquiring the nuclear magnetic resonance measurement uses a polarization time sufficiently long so that nuclear spins are substantially polarized.
4. (Original) The method of claim 1, wherein the dielectric measurement comprises an electromagnetic wave phase shift.
5. (Original) The method of claim 1, wherein the formation fluids comprise fluids in a formation traversed by a borehole drilled with a water-based drilling fluid.
6. (Original) The method of claim 5, wherein the acquiring the nuclear magnetic resonance measurement and the acquiring the dielectric measurement are performed while drilling.
7. (Original) The method of claim 5, further comprising:
 - determining a water-filled porosity from the dielectric measurement;

8. (Original) The method of claim 5, wherein the dielectric measurement comprises an electromagnetic wave attenuation.
9. (Original) The method of claim 8, further comprising:
 - determining a total formation porosity from the nuclear magnetic resonance measurement; and
 - calculating a salinity of a brine in the formation based on the total formation porosity and a known aqueous phase attenuation function with respect to the salinity and a formation temperature.
10. (Original) The method of claim 1, wherein the formation fluids comprise at least one sample withdrawn from a formation traversed by a borehole, and a sum of an oil volume fraction and a water volume fraction is taken to be one.
11. (Original) The method of claim 10, further comprising:
 - determining a total volume of the formation fluids from the nuclear magnetic resonance measurement;
 - determining the water volume fraction of the formation fluids from the dielectric measurement; and
 - determining the oil volume fraction of the formation fluids by subtracting the water volume fraction of the formation fluids from the total volume of the formation fluids.
12. (Original) The method of claim 10, wherein the dielectric measurement comprises an electromagnetic wave attenuation.
13. (Original) The method of claim 12, further comprising calculating a salinity of a brine in the sample based on a total volume of the formation fluids and a known aqueous

acquiring a nuclear magnetic resonance measurement of an earth formation;
acquiring a dielectric measurement of the earth formation;
acquiring a bulk density measurement of the earth formation; and
forming a set of linear response equations representing a reservoir fluid model;

and

solving ~~a~~ the set of linear response equations ~~representing a reservoir fluid model~~ to determine fractional fluid volumes of the earth formation from a combination of the nuclear magnetic resonance measurement, the dielectric measurement, and the bulk density measurement.

15. (Original) The method of claim 14, wherein the reservoir fluid model comprises a representation of a non-gas bearing formation, the fractional fluid volumes comprise a water volume fraction, an oil volume fraction, and an oil-based mud filtrate volume fraction, and the set of linear response equations comprises:

a nuclear magnetic resonance response equation that defines a total volume of the formation fluids with respect to the oil volume fraction, the water volume fraction, and the oil-based mud filtrate volume fraction.

a dielectric response equation that defines an electromagnetic wave travel time with respect to the oil volume fraction and an oil travel time, the water volume fraction and a water travel time, and the oil-based mud filtrate volume fraction and an oil-based mud filtrate travel time; and

a density response equation that defines the bulk density with respect to an oil density and the oil volume fraction, a water density and the water volume fraction, and an oil-based mud filtrate density and the oil-based mud filtrate volume fraction.

16. (Original) The method of claim 15, wherein the formation fluids comprise fluids in a

filled porosity, the water volume fraction comprises a water-filled porosity, and the oil-based mud filtrate volume fraction comprises an oil-based mud filtrate porosity.

17. (Original) The method of claim 16, wherein the oil-filled porosity and the oil-based mud filtrate porosity are inseparable and the reservoir fluid model comprises a water phase and a combined oil and oil-based mud filtrate phase.
18. (Original) The method of claim 16, wherein the dielectric measurement comprises a measurement of a complex dielectric constant of the formation.
19. (Original) The method of claim 16 further comprising calculating a salinity of a connate water in the formation based on the total formation porosity and a known aqueous phase attenuation function with respect to the salinity and a formation temperature.
20. (Original) The method of claim 15, wherein the formation fluids comprise at least one sample taken from a formation traversed by a borehole, and a sum of the oil volume fraction, the water volume fraction, and the oil-based mud filtrate volume fraction is taken to be one.
21. (Original) The method of claim 20, wherein the at least one sample is withdrawn such that it comprises substantially native formation fluids and the oil-based mud filtrate volume fraction is zero.
22. (Original) The method of claim 14, wherein the reservoir fluid model comprises a representation of a gas-bearing formation, the fractional fluid volumes comprise a gas volume fraction, a water volume fraction, and a gas-corrected total volume, and the set of linear regression equations comprises:

a dielectric response equation that is adapted for the gas-bearing formation by defining an electromagnetic wave travel time with respect to the gas volume fraction and a gas travel time, the water volume fraction and a water travel time, and the gas-corrected total volume and a gas-corrected travel time; and

a density response equation that is adapted for the gas-bearing formation by defining the bulk density measurement with respect to the gas volume fraction and a gas density, the water volume fraction and a water density, and the gas-corrected total volume and a gas-corrected total density.

23. (Original) The method of claim 22, wherein the formation fluids comprise fluids in a formation traversed by a borehole, the electromagnetic wave travel time is a formation electromagnetic wave travel time, the bulk density comprises a formation bulk density, the total volume of the formation fluids comprises a total formation porosity, the gas volume fraction comprises a gas-filled porosity, the water volume fraction comprises a water-filled porosity, and the gas-corrected total volume comprises a gas-corrected total formation porosity.
24. (Original) The method of claim 22, wherein the formation fluids comprise at least one sample taken from a formation traversed by a borehole, and a sum of the gas-filled porosity and the water-filled porosity is taken to be one.
25. (Withdrawn)
26. (Withdrawn)
27. (Withdrawn)
28. (Once Amended) A method for making formation evaluation determinations

determining a rock-matrix travel time associated with the earth formation from a combination of the nuclear magnetic resonance measurement and the dielectric measurement.

29. (Original) The method of claim 28, further comprising determining a rock-matrix travel time log as a function of borehole depth.

30. (Once Amended) A method for ~~evaluating~~ determining a gas fractional volume in a gas-liquid sample, comprising:

acquiring a bulk density measurement of the gas-liquid sample;

acquiring a nuclear magnetic resonance measurement of the gas-liquid sample;

and

determining the gas fractional volume of the gas-liquid sample from a combination of the bulk density measurement and the nuclear magnetic resonance measurement.

31. (Original) The method of claim 30, further comprising computing a density porosity from the bulk density measurement and a fluid density, and wherein the determining the gas fractional volume is performed using the density porosity and the nuclear magnetic resonance measurement.

32. (Once Amended) A method for making formation evaluation determinations ~~evaluating a formation traversed by a borehole,~~ comprising:

acquiring a dielectric measurement of an earth formation;

determining a dielectric-derived water volume of the earth formation from the dielectric measurement;

acquiring a suite of nuclear magnetic resonance measurements of the earth

comparing the dielectric-derived water volume with the nuclear magnetic resonance derived water volume and the apparent oil volume to produce a true heavy oil volume of the earth formation.